


Helios Transparent Led Wall

LED Trasparent Screen with Side Emitting Technology



Screen Size

1000 × 500

Application Scenarios

Stage rental business

Helios Transparent Led Wall

Transparency: 82%Brightness: 5000cd/m²

· Depth: 38mm

· Viewing Angle: 120°



Light Penetrate



SMD Ideal for Stage Viewing Angle



8 Pin Vibration -proof Port



SMD on surface of the bar -avoid lamps being knocked off



Modularized Power Supply



Different batches can be mixed to use



120° Wide Viewing Angle




System Stable

Why Side Light-Emitting Technical

Higher Transparency

85% Transparency

Sun Digital Helios Screen making many special stage effect possible: three-dimensional stage, images look like appearing in the sky directly etc.



Easy Installation

Slim and light

Light, UP to 17 Kg/m²:Thin, UP to 38 mm; The Sun Digital Helios Screen is unbelievably lightweight and thin.



Modularized | DIY design

Any size screen combination flexible, no steel structure, no complicated installation, easy and convenient.



Easy Maintain

All-in-One Design

Integration of control system and power supply into one module, easy and fast installation, uninstallation and maintenance.

SUN DIGITAL



OTHER





Key Features

High refresh rate

High refresh rate: in the industry, the minimum pixel pitch (able to mass production) 3mm, 3840HZ refresh rate.

3840HZ



60HZ

Light Penetrate

Light can penetrate without affecting stage lighting effect.



8 Pin Vibration-Proof Port

No screen flash affected by audio vibration.



Smart

Smart control by mobile APP, wireless data transmission, screen+data cloud+APP, WIFI connection.








Different batches can be mixed to use

Different batches, not too much visual difference, can be put around the main screen.




System Stable


Main controller has good compatibility, on-site system is stable.



Die casting aluminum structure

Die casting aluminum structure will not be deformed even after frequent installation and uninstallation.





Simple


No complicated installation, No steel structure, fast positioning and fast installation, convenient and quick maintenance.






Helios

1000 × 500 × 78 / 8.5 Kg







Transparent LED rental screen is a new type of LED display with features like transparent display, easy to install and disassemble, smart control etc. A totally new, irreplaceable, creative application effect can be realized by using transparent led screen in concert, TV station's party & large entertainment program, auto show & high-end exhibition, and large-scale new product launch conference etc.

Specifications

 Size (mm)
 1000X 500

 Model
 I3

 Pixel Pitch (mm)
 3.9 x 7.8

 Pixel Density (dot/m²)
 32768

 Module Resolution (dot)
 256 X 64

 LED Type
 SMD 3 in 1

 Brightness (cd/m²)
 5000

 Transparency
 82%

 Viewing Angle
 120

 Grey Level
 14bits

 Scan Mode
 1/4


LED Type	SMD 3 in 1
Brightness (cd/m²)	5000
Transparency	82%
Viewing Angle	120
Grey Level	14bits
Scan Mode	1/4
Refesh Rate (Hz)	3840
Frame Frequency (Hz)	60
Avg.Power Consumption(W/ m²)	240
Max.Power Consumption(W/ m²)	800
Maintenance	Back
IP	IP42
Working Temp	-20~50℃
Weight (kg/ m²)	17




Helios

Connectivity

- 1 POWER
- 2 LAN



2 Types of Installation



Hang



System topology

